

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1-3. (Canceled)

4. (Currently Amended) A routing method in a data processing system comprising the steps of:

receiving a data packet;

retrieving a destination address from the data packet;

hashing the destination address to determine a table index into a table in a computer readable medium;

reading a target address from a table entry using the table index, wherein the target address has been related to and stored in the table entry based on a computed value from a relation computation using the table index and the target address as operands in the relation computation;

modifying the data packet by storing the target address in the data packet ~~as a next hop destination address~~; and

transmitting the modified data packet.

5. (Currently Amended) The method of claim 4, further comprising a step of relating a particular table entry to a target address in which:

for each target address in the set of target addresses, generating a computed value using the table index for the particular entry and a target address as operands in the relation computation to obtain a set of computed values;

choosing a computed value from the set of computed values based upon a mathematical relationship among the set of computed values; and

determining a related target address for the particular entry based on the chosen computed value, wherein the chosen computed value was computed using the related-target address as input.

6. (Currently Amended) The method of claim 5, further comprising:
obtaining a set of target addresses;
for each table entry, relating a target address from the set of target addresses to a table entry such that each table entry is related with only one target address; and
for each table entry, storing in a table entry its related target address.
7. (Currently Amended) A method in a data processing system for mapping a source identifier to a target identifier in a set of target identifiers, the method comprising the steps of:
managing a data structure in a computer readable medium, wherein each entry within the data structure stores information associated with a single target identifier and wherein a single target identifier is related to one or more entry locations;
hashing the source identifier to a location identifier of an entry in the data structure;
retrieving information associated with the target identifier from the entry in the data structure using the location identifier; and
obtaining a mapped target identifier from the retrieved information associated with the target identifier, [[and]]
wherein a processing speed with which the source identifier is mapped to the mapped target identifier is independent of a total number of target identifiers in the set of target identifiers.
8. (Currently Amended) The method of claim 7, wherein the method for mapping the source identifier to the target identifier is stable with respect to changes in the set of target identifiers.
9. (Original) A method in a data processing system for mapping a source identifier to a target identifier, the method comprising the steps of:
hashing the source identifier to determine a table index into a table in a computer readable medium; and
reading the target identifier from a table entry using the table index, wherein the target identifier has been related to and stored in the table entry based on a computed value from a relation computation using the table index and the target identifier as operands in the relation computation.

10. (Currently Amended) The method of claim 9₁ further comprising a step of relating a particular table entry to a target identifier in which:

for each target identifier in the set of target identifiers, generating a computed value using the table index for the particular table entry and a target identifier as operands in the relation computation to obtain a set of computed values;

choosing a computed value from the set of computed values based upon a mathematical relationship among the set of computed values; and

determining a related target identifier for the particular entry based on the chosen computed value, wherein the chosen computed value was computed using the related target identifier as input.

11. (Currently Amended) The method of claim 10₁ further comprising, prior to the step of reading the target identifier from the table entry:

obtaining a set of target identifiers;

for each table entry, relating a target identifier from the set of target identifiers to a table entry such that each table entry is related with only one target identifier; and

for each table entry, storing in a table entry its related target identifier.

12. (Currently Amended) The method of claim 10₁ further comprising:

dynamically removing a target identifier from a set of target identifiers to obtain a modified set of target identifiers;

for each table entry previously related to the removed target identifier, newly relating a target identifier from the modified set of target identifiers to a table entry such that each table entry is related with only one target identifier; and

for each table entry previously related to the removed target identifier, storing in a table entry its newly related target identifier.

13. (Currently Amended) The method of claim 10₁ further comprising:
dynamically adding a target identifier to a set of target identifiers to obtain a modified set of target identifiers;
for each table entry, relating a target identifier from the modified set of target identifiers to a table entry such that each table entry is related with only one target identifier; and
for each table entry, storing in a table entry its related target identifier if its related target identifier differs from a target identifier previously stored in the table entry.
14. (Currently Amended) The method of claim 9₁ wherein the relation computation further comprises:
receiving the table index and the target identifier as operands for the relation computation;
hashing the table index to generate a first hash value;
hashing the target identifier to generate a second hash value; and
hashing the first hash value and the second hash value to generate a computed value.
15. (Currently Amended) The method of claim 9₁ further comprising:
obtaining a set of target identifiers, wherein each target identifier identifies a computational resource such that each target identifier is related with only one computational resource.
16. (Currently Amended) The method of claim 9₁ further comprising:
associating a computational resource with a subset of a set of target identifiers, wherein each target identifier in the set of target identifiers is related with only one computational resource, wherein each target identifier in the subset of target identifiers identifies the computational resource, and wherein a size of the subset of target identifiers is proportional to a computational capacity of the computational resource.
17. (Currently Amended) The method of claim 9₁ wherein the source identifier is a network protocol address.

18. (Currently Amended) The method of claim 9₁ wherein the target identifier is a network physical address.

19. (Currently Amended) The method of claim 9₁ wherein the target identifier is a Uniform Resource Identifier (URI).

20-41. (Canceled)

42. (Currently Amended) A method in a data processing system for mapping a source identifier to a target identifier, the method comprising [[the]] steps of:

hashing the source identifier to determine a location identifier of an entry in a data structure in a computer readable medium; and

reading information associated with the target identifier from the entry in the data structure using the location identifier, wherein the information associated with the target identifier has been related to and stored in the entry based on a computed value from a relation computation using the location identifier and the target identifier as operands in the relation computation.

43. (Currently Amended) The method of claim 42₁ further comprising a step of relating a particular entry in the data structure to a target identifier in which:

for each target identifier in the set of target identifiers, generating a computed value using the location identifier of the particular entry in the data structure and a target identifier as operands in the relation computation to obtain a set of computed values;

choosing a computed value from the set of computed values based upon a mathematical relationship among the set of computed values; and

determining a related target identifier for the particular entry based on the chosen computed value, wherein the chosen computed value was computed using the related target identifier as input.

44. (Currently Amended) The method of claim 43, further comprising, prior to the step of reading the information associated with the target identifier from the entry in the data structure:

obtaining a set of target identifiers; [[and]]

for each entry in the data structure, relating a target identifier from the set of target identifiers to an entry in the data structure such that each entry in the data structure is related with only one target identifier; and

for each entry in the data structure, storing in an entry information associated with its related target identifier.

45. (Currently Amended) The method of claim 43, further comprising:

dynamically removing a target identifier from a set of target identifiers to obtain a modified set of target identifiers;

for each entry in the data structure previously related to the removed target identifier, newly relating a target identifier from the modified set of target identifiers to an entry in the data structure such that each entry in the data structure is related with only one target identifier; and

for each entry in the data structure previously related to the removed target identifier, storing in an entry information associated with its newly related target identifier.

46. (Currently Amended) The method of claim 43, further comprising:

dynamically adding a target identifier to a set of target identifiers to obtain a modified set of target identifiers;

for each entry in the data structure, relating a target identifier from the modified set of target identifiers to an entry in the data structure such that each entry in the data structure is related with only one target identifier; and

for each entry in the data structure, storing in an entry information associated with its related target identifier if its related target identifier differs from a target identifier previously related to the entry in the data structure.

47. (Currently Amended) The method of claim 42, wherein the relation computation further comprises:

receiving the location identifier and the target identifier as operands for the relation computation;

hashing the location identifier to generate a first hash value;

hashing the target identifier to generate a second hash value; and

hashing the first hash value and the second hash value to generate a computed value.

48. (Currently Amended) The method of claim 42, further comprising:

obtaining a set of target identifiers, wherein each target identifier identifies a computational resource such that each target identifier is related with only one computational resource.

49. (Currently Amended) The method of claim 42, further comprising:

associating a computational resource with a subset of a set of target identifiers, wherein each target identifier in the set of target identifiers is related with only one computational resource, wherein each target identifier in the subset of target identifiers identifies the computational resource, and wherein a size of the subset of target identifiers is proportional to a computational capacity of the computational resource.

50. (Currently Amended) The method of claim 42, further comprising:

retrieving the target identifier using the information associated with the target identifier;
and

performing a computational process on a computational resource identified by the target identifier.

51. (Currently Amended) The method of claim 50, wherein the computational resource identified by the target identifier is a memory resource.

52. (Currently Amended) The method of claim 50, wherein the computational resource identified by the target identifier is a data processing system.

53. (Currently Amended) The method of claim 42, wherein the information associated with the target identifier comprises the target identifier.
54. (Currently Amended) The method of claim 42, wherein the data structure is a table, and the location identifier is a table index.
55. (Currently Amended) The method of claim 42, wherein the source identifier is a network protocol address.
56. (Currently Amended) The method of claim 42, wherein the target identifier is a network physical address.
57. (Currently Amended) The method of claim 42, wherein the target identifier is a Uniform Resource Identifier (URI).
58. (Currently Amended) A[[[n]]] ~~apparatus~~ data processing system [[[for]]] that enables a mapping of a source identifier to a target identifier, the data processing system comprising a processor and a memory comprising instructions, which when executed, perform actions comprising:
- ~~first hashing means for~~ hashing the source identifier to determine a location identifier of an entry in a data structure in a computer readable medium; and
- ~~reading means for~~ reading information associated with the target identifier from the entry in the data structure using the location identifier, wherein the information associated with the target identifier has been related to and stored in the entry based on a computed value from a relation computation using the location identifier and the target identifier as operands in the relation computation.

59. (Currently Amended) The ~~apparatus~~ data processing system of claim 58, further comprising first relating means for relating a particular entry in the data structure to a target identifier wherein:

~~generating means for~~ generating, for each target identifier in the set of target identifiers, a computed value using the location identifier of the particular entry in the data structure and a target identifier as operands in the relation computation to obtain a set of computed values;

~~choosing means for~~ choosing a computed value from the set of computed values based upon a mathematical relationship among the set of computed values; and

~~determining means for~~ determining a related target identifier for the particular entry based on the chosen computed value, wherein the chosen computed value was computed using the related target identifier as input.

60. (Currently Amended) The ~~apparatus~~ data processing system of claim 59, further comprising, prior to the step of reading the information associated with the target identifier from the entry in the data structure:

~~first obtaining means for~~ obtaining a set of target identifiers; [[and]]

~~second relating means for~~ relating, for each entry in the data structure, a target identifier from the set of target identifiers to an entry in the data structure such that each entry in the data structure is related with only one target identifier; and

~~first storing means for~~ storing, in each entry in the data structure, information associated with its related target identifier.

61. (Currently Amended) The ~~apparatus~~ data processing system of claim 59, further comprising:

~~removing means for~~ dynamically removing a target identifier from a set of target identifiers to obtain a modified set of target identifiers;

~~third relating means for~~ newly relating, for each entry in the data structure previously related to the removed target identifier, a target identifier from the modified set of target identifiers to an entry in the data structure such that each entry in the data structure is related with only one target identifier; and

~~second storing means for~~ storing, in each entry in the data structure previously related to the removed target identifier, information associated with its newly related target identifier.

62. (Currently Amended) The ~~apparatus~~ data processing system of claim 59, further comprising:

~~adding means for~~ dynamically adding a target identifier to a set of target identifiers to obtain a modified set of target identifiers; [[and]]

~~fourth relating means for~~ relating, for each entry in the data structure, a target identifier from the modified set of target identifiers to an entry in the data structure such that each entry in the data structure is related with only one target identifier; and

~~third storing means for~~ storing, in each entry in the data structure, information associated with its related target identifier if its related target identifier differs from a target identifier previously related to the entry in the data structure.

63. (Currently Amended) The ~~apparatus~~ data processing system of claim 58, wherein the relation computation further comprises:

~~receiving means for~~ receiving the location identifier and the target identifier as operands for the relation computation;

~~second hashing means for~~ hashing the location identifier to generate a first hash value;

~~third hashing means for~~ hashing the target identifier to generate a second hash value; and

~~fourth hashing means for~~ hashing the first hash value and the second hash value to generate a computed value.

64. (Currently Amended) The ~~apparatus~~ data processing system of claim 58, further comprising:

~~second~~ obtaining a set of target identifiers, wherein each target identifier identifies a computational resource such that each target identifier is related with only one computational resource.

65. (Currently Amended) The ~~apparatus~~ data processing system of claim 58, further comprising:

~~associating means for~~ associating a computational resource with a subset of a set of target identifiers, wherein each target identifier in the set of target identifiers is related with only one computational resource, wherein each target identifier in the subset of target identifiers identifies the computational resource, and wherein a size of the subset of target identifiers is proportional to a computational capacity of the computational resource.

66. (Currently Amended) The ~~apparatus~~ data processing system of claim 58, further comprising:

~~retrieving means for~~ retrieving the target identifier using the information associated with the target identifier; and

~~performing means for~~ performing a computational process on a computational resource identified by the target identifier .

67. (Currently Amended) The ~~apparatus~~ data processing system of claim 64, wherein the computational resource identified by the target identifier is a memory resource.

68. (Currently Amended) The ~~apparatus~~ data processing system of claim 64, wherein the computational resource identified by the target identifier is a ~~data processing system~~ router.

69. (Currently Amended) The ~~apparatus~~ data processing system of claim 58, wherein the information associated with the target identifier comprises the target identifier.

70. (Currently Amended) The ~~apparatus~~ data processing system of claim 58, wherein the data structure is a table, and the location identifier is a table index.

71. (Currently Amended) The ~~apparatus~~ data processing system of claim 58, wherein the source identifier is a network protocol address.

72. (Currently Amended) The ~~apparatus~~ data processing system of claim 58, wherein the target identifier is a network physical address.

73. (Currently Amended) The ~~apparatus~~ data processing system of claim 58, wherein the target identifier is a Uniform Resource Identifier (URI).

74. (Currently Amended) A computer program product ~~[[on]]~~ comprising a computer readable medium including instructions, which when executed for use in a data processing system, ~~[[for]]~~ map~~[[ping]]~~ a source identifier to a target identifier, the computer program product comprising:

- instructions for hashing the source identifier to determine a location identifier of an entry in a data structure in a computer readable medium; and

- instructions for reading information associated with the target identifier from the entry in the data structure using the location identifier, wherein the information associated with the target identifier has been related to and stored in the entry based on a computed value from a relation computation using the location identifier and the target identifier as operands in the relation computation.

75. (Currently Amended) The computer program product of claim 74, further comprising instructions ~~[[for]]~~ relating a particular entry in the data structure to a target identifier including:

- instructions for generating, for each target identifier in the set of target identifiers, a computed value using the location identifier of the particular entry in the data structure and a target identifier as operands in the relation computation to obtain a set of computed values;

- instructions for choosing a computed value from the set of computed values based upon a mathematical relationship among the set of computed values; and

- instructions for determining a related target identifier for the particular entry based on the chosen computed value, wherein the chosen computed value was computed using the related target identifier as input.

76. (Currently Amended) The computer program product of claim 75₁ further comprising:
instructions for obtaining a set of target identifiers; [[and]]
instructions for relating, for each entry in the data structure, a target identifier from the set of target identifiers to an entry in the data structure such that each entry in the data structure is related with only one target identifier; and
instructions for storing, in each entry in the data structure, information associated with its related target identifier.
77. (Currently Amended) The computer program product of claim 75₁ further comprising:
instructions for dynamically removing a target identifier from a set of target identifiers to obtain a modified set of target identifiers;
instructions for newly relating, for each entry in the data structure previously related to the removed target identifier, a target identifier from the modified set of target identifiers to an entry in the data structure such that each entry in the data structure is related with only one target identifier; and
instructions for storing, in each entry in the data structure previously related to the removed target identifier, information associated with its newly related target identifier.
78. (Currently Amended) The computer program product of claim 75₁ further comprising:
instructions for dynamically adding a target identifier to a set of target identifiers to obtain a modified set of target identifiers; [[and]]
instructions for relating, for each entry in the data structure, a target identifier from the modified set of target identifiers to an entry in the data structure such that each entry in the data structure is related with only one target identifier; and
instructions for storing, in each entry in the data structure, information associated with its related target identifier if its related target identifier differs from a target identifier previously related to the entry in the data structure.

79. (Currently Amended) The computer program product of claim 74₁ wherein the relation computation further comprises:

instructions for receiving the location identifier and the target identifier as operands for the relation computation;

instructions for hashing the location identifier to generate a first hash value;

instructions for hashing the target identifier to generate a second hash value; and

instructions for hashing the first hash value and the second hash value to generate a computed value.

80. (Currently Amended) The computer program product of claim 74₁ further comprising:

instructions for obtaining a set of target identifiers, wherein each target identifier identifies a computational resource such that each target identifier is related with only one computational resource.

81. (Currently Amended) The computer program product of claim 74₁ further comprising:

instructions for associating a computational resource with a subset of a set of target identifiers, wherein each target identifier in the set of target identifiers is related with only one computational resource, wherein each target identifier in the subset of target identifiers identifies the computational resource, and wherein a size of the subset of target identifiers is proportional to a computational capacity of the computational resource.

82. (Currently Amended) The computer program product of claim 74₁ further comprising:

instructions for retrieving the target identifier using the information associated with the target identifier; and

instructions for performing a computational process on a computational resource identified by the target identifier.

83. (Currently Amended) The computer program product of claim 80₁ wherein the computational resource identified by the target identifier is a memory resource.

84. (Currently Amended) The computer program product of claim 80₁ wherein the computational resource identified by the target identifier is a data processing system.

85. (Currently Amended) The computer program product of claim 74₂ wherein the information associated with the target identifier comprises the target identifier.

86. (Currently Amended) The computer program product of claim 74₂ wherein the data structure is a table, and the location identifier is a table index.

87-89. (Canceled)

90. (Currently Amended) A routing method in a data processing system comprising [[the]] steps of:

- receiving a data packet;

- retrieving a destination address from the data packet;

- hashing the destination address to determine a table index into a table in a computer readable medium;

- reading a target address from a table entry using the table index, wherein the target address has been related to and stored in the table entry based on a computed value from a relation computation using the table index and the target address as operands in the relation computation, wherein the relation computation is a nearness function;

- modifying the data packet by storing the target address in the data packet ~~as a next hop destination address~~; and

- transmitting the modified data packet.

91. (Currently Amended) The method of claim 90₁ further comprising a step of relating a particular table entry to a target address in which:

- for each target address in the set of target addresses, generating a computed value using the table index for the particular entry and a target address as operands in the relation computation to obtain a set of computed values;

- choosing a computed value from the set of computed values based upon a mathematical relationship among the set of computed values; and

- determining a related target address for the particular entry based on the chosen computed value, wherein the chosen computed value was computed using the related-target address as input.

92. (Currently Amended) The method of claim 91, further comprising:
- obtaining a set of target addresses;
 - for each table entry, relating a target address from the set of target addresses to a table entry such that each table entry is related with only one target address; and
 - for each table entry, storing in a table entry its related target address.